

# IV rod

**02594** The IV rod on synthetic or aluminium base is height-adjustable and easy to move.

## Support

- The support consists of an adjustable part  $\varnothing$  19 mm and is equipped with stainless steel hooks.
- The fixed tube has a diameter of 25 mm (synthetic base) or 32 mm (aluminium base) is firmly mounted on a five-legged base.
- The adjustable pole glides into a synthetic fluid-sealing tube (when equipped with an aluminium base).
- The adjustable pole is fastened with a knob.
- The IV rod can be optionally equipped with a drip catcher and a holder.
- All steel parts are finished with a chromium-plated layer.
- The aluminium base is polished.
- The IV rod is equipped with 5 design castors  $\varnothing$  80 mm, of which two have brakes.




## Dimension

### 02594 | synthetic base

- Adjustable height: 130 to 200 cm.
- Synthetic base: 59 cm.
- Maximum load: 2 kg/hook (max. 8 kg in total).

### 02594 | aluminium base

- Adjustable height: 155 to 200 cm.
- Aluminium base: 61 cm.
- Maximum load: 2 kg/hook (max. 8 kg in total).



## Materials and finishing

- Metal: steel, chrome.
- Synthetic.
- Resistant to the common cleaning products

For further information about used materials, constructions and maintenance: consult our materialfiles.

